

E8TURBOVZ

HD 1080p Turbo HD Dome Camera

epcom®



► Camera

Image Sensor	2MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1928 (H) *1088 (V)
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25s to 1/50,000 s
Lens	Motorized VF lens; 2.8 - 12 mm @ F1.2
Lens Mount	φ14
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 25 fps / 1080p @ 30 fps
HD Video Output	1 Analog HD output
S/N Ratio	62 dB

► General

Working Temperature/ Humidity	-40°C-60°C (-40°F-140°F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 6 W
Weather Proof Ratings	IP66
IR Range	Up to 40 m
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	134.3 × 123.9 × 111.4 mm (5.29"×4.88"×4.39")
Weight	Approx. 750 g (1.57 lb)

► Menu

AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR

► Key Features

2 Megapixel high-performance CMOS

Analog HD output, up to 1080P resolution

2.8mm-12mm motorized vari-focal lens

True Day/Night

OSD menu, DNR, Smart IR

True WDR, up to 120dB

EXIR technology, up to 40m IR distance

IP66 weatherproof IP66

EXIR technology, up to 40m IR distance

TURBOHD ► series